

► **Specifications**

377 HP STERNDRIVE • MPI



▼ **Features**

- Balanced and blueprinted, multiport-injected V-8 produces 400 foot-pounds of torque.
- Specialty engine components, including a high-lift hydraulic camshaft, aluminum rocker arms, stainless steel intake and exhaust valves, balanced forged-steel crankshaft, and lightweight aluminum-alloy pistons, enhance power and torque throughout the engine's operating range.
- MEFI 3 Electronic Control Module digital ignition system features advanced electronics for more precise fuel and spark control along with better top-end throttle response.
- Powerful 65-amp/917-watt alternator provides dependable starting and additional power for operating electrical accessories.
- A one-piece serpentine belt system requires less horsepower to drive engine accessories.
- Water-cooled and insulated fuel system helps keep fuel temperatures down and greatly reduces potential for vapor lock with today's fuels.
- Comes standard with 1.36:1 or 1.50:1 gear ratio – Bravo One® drive.
- Integrated Transom System (ITS) available with Bravo One XR™ and Bravo One XR Sport Master drive options.

► **Features**

377 HP STERNDRIVE • MPI

▼ **Specifications**

Crankshaft Rated Horsepower (HP/kW)	377/294
Full-Throttle RPM Range	4800 – 5200
Displacement Liter/CID	6.2/377
Bore & Stroke (in)	4.00 x 3.75
Bore & Stroke (mm)	102 x 95
Compression Ratio	9:1
Cylinder/Configuration	V-8
Alternator Amp	65
Alternator Watt	917
Fuel System	MPI
Ignition System	Digital
Fuel Requirements	92 Posted Octane (R+M)/2 (98 RON)
Drive Options	Bravo One, Bravo One XR, Bravo One XR w/ITS, Bravo One XR Sport Master, Bravo One XR Short Sport Master, Bravo One XR Sport Master w/ITS, and Bravo One XR Short Sport Master w/ITS
Drive/Gear Ratios	Bravo One – 1.36:1, 1.50:1
Drive/Gear Ratios	Bravo One XR/Bravo One XR Sport Master (Standard and Short) 1.26:1, 1.35:1, 1.50:1
Length (in/mm)	37/940
Width (in/mm)	29/737
Height (in/mm)	20/508
Weight (lb/kg)	969/441
Warranty	1-Year Ltd. for Recreational Boating/3-Year Ltd. Corrosion

EFFECTIVE JULY 2003

Option availability determined by boat manufacturers within their boat model offerings. All models and specifications are subject to change without notice or incurring obligation to modify previously manufactured products.